

Effective and Economical Hydrocarbon Removal with Enhanced Polymeric Absorbent Cartridges

Parker Fulflo® TruBind absorbent cartridges utilize a modified polymeric absorbent that economically and effectively reduces trace hydrocarbon contamination in aqueous fluids. The enhanced polymer, configured in a radial-flow-design cartridge, provides maximum utilization of available surface area. This product can be used alone or as an enhancement to other systems. Whether process fluid reclamation or meeting disposal requirements is the goal, TruBind can solve many demanding hydrocarbon-contaminated aqueous fluid problems.

Applications

- Water Soluble Machine Tool Coolants
- Alkaline Parts Washing
- Industrial Discharge Water
- Produced Water Disposal
- Injection Molding Cooling Water
- E-Coat Paint
- Pre R.O. Membrane
- Tanker Ballast Water
- Aerosol Mists
- Plating Bath
- Leisure/Commercial Shipping Bilge Water
- Surface Water Runoff (Truck stops, airports, auto service stations)
- Gas & Oil Facility Wastewater
- Car & Truck Wash Water
- Compressor Condensate
- Post Oil/Water Separator Polishing
- Floor Scrubbing Waste Water
- Pre Carbon Bed



Features and Benefits

- Increases machine tool life when installed at point-of-use
- Increases working life of valuable process fluids.
- Reduces hydrocarbon levels to meet EPA discharge regulations.
- Absorbed hydrocarbon is chemically bound by polymer and is not leachable.
- Absorbent polymer is enhanced to maximize utilization of surface area.
- Radial flow design of cartridge allows maximum flow with minimal pressure drop.
- High integrity construction withstands harsh process environment.
- A variety of cartridge sizes and end cap options increase housing selection.
- TruBind cartridges are completely incinerable.
- Parker's TQM system assures consistent and reliable performance.

Process Filtration Division

WARNING! FAILURE OR IMPROPER SELECTION OR IMPROPER USE OF THE PRODUCTS AND/OR SYSTEMS DESCRIBED HEREIN OR RELATED ITEMS CAN CAUSE DEATH, PERSONAL INJURY AND PROPERTY DAMAGE. This document and other information from Parker Hannifin Corporation, its subsidiaries and authorised distributors provide product and/or system options for further investigation by users having technical expertise. It is important that you analyse all aspects of your application and review the information concerning the product or system in the current product catalogue. Due to the variety of operating conditions and applications for these products or systems, the user, through its own analysis and testing, is solely responsible for making the final selection for the products and systems and assuring that all performance, safety and warning requirements of the application are met. The products described herein, including without limitation, product features, specifications, designs, availability and pricing, are subject to change by Parker Hannifin Corporation and its subsidiaries at any time without notice.

Absorbent Series

Technology

Unlike competitive technologies in which hydrocarbons are removed through surface adsorption onto the medium, TruBind cartridges utilize a proprietary modified polymer that both absorbs and binds the hydrocarbon molecules into its interior matrices. The affinity of the polymeric absorbent for hydrocarbon contaminant is so great that accelerated testing by the Toxic Characteristics Leachate Procedure (TCLP) indicated the effluent hydrocarbon level in water to be below current and proposed EPA

limits. The modified polymer was formulated to control the speed of hydrocarbon absorption by eliminating the potential for skin formation at the polymer/hydrocarbon interface. Consequently this polymer, when incorporated into a radial-flow-design cartridge, insures maximum utilization of surface area. The nature of the polymer makes it an effective absorbent of free, emulsified and dissolved oils, synthetic lubricants, grease and a multitude of organic solvents.

Performance

TruBind absorbent cartridge efficiency depends upon the residence time of the fluid within the cartridge, which is a function of the volumetric flow rate.

1. Hydrocarbon Removal Efficiency: At an equivalent flow rate of 3.78 l/min per 254mm cartridge the TruBind cartridge typically reduces trace hydrocarbon contaminant in excess of 95% in single pass mode. This efficiency level can be maintained only to a net differential pressure of 0.69 bar. Series or multipass filtration can virtually eliminate hydrocarbon contamination.

2. Hydrocarbon Absorbent Capacity: The

TruBind cartridge medium has the potential to remove up to 250 grams (approximately one-half pint) of low density hydrocarbon contaminant. On this basis, the table below provides expected life data in hours or gallons at several trace contaminant levels based on a 3.78 l/min flow rate per 254mm cartridge. Absorbent capacity will decrease as density of hydrocarbon increases.

3. Flow Rate Capability: A maximum flow rate of 3.78 l/min per 254mm length cartridge is recommended for the most effective removal of trace hydrocarbon contaminant.

Hydrocarbon Concentration (ppm)	Hydrocarbon Concentration (% by Weight)	Hydrocarbon Removal per Minute (grams)	Estimated Life in Hours	Litres Fluid Treated
10	.001	0.04	106.0	23,959
100	.01	0.40	10.6	2,395
1,000	.1	4.00	1.1	238

Specifications

Materials of Construction:

- Absorbent: Proprietary modified polymer
- Support Construction: 100% polyolefin
- Seal Material: Gasket (Polyethylene Foam); 222 O-Ring (Buna-N)

Cartridge Dimensions (nominal)

- Lengths: 10-40 in (249mm-1016mm)
- Outside Diameter: 2-1/2 in (63.5 mm)
- Inside Diameter: 1-1/16 in (27 mm)

Maximum Recommended Operating Conditions:

- Temperature: 150°F (65°C)@20 psid (1.4 bar)
- Pressure: 60 psid (4.1 bar) @ 75°F (24°C)
- Flow Rate: 1.0 gpm per 10-inch cartridge
- Changeout Pressure Drop (net): 10 psi (0.7 bar)
- Flow Factor: 0.00r band per l/min at 1 cks viscosity per 254mm cartridge

BioSafety:

- The TruBind cartridge is classified as non-hazardous and incinerable. Disposal must be dictated by local regulations pertaining to the absorbed contaminant.

Consult factory for product configurations

Ordering Information

<p>TBC</p> <p>Cartridge Series</p> <p>TruBind Absorbent Cartridge</p> <p>Example: TBC10A-TC-A</p>	<p>10</p> <p>Cartridge Length</p> <table border="0"> <tr> <td><u>Code</u></td> <td><u>in</u></td> <td><u>mm</u></td> </tr> <tr> <td>9</td> <td>9-5/8</td> <td>244</td> </tr> <tr> <td>10</td> <td>9-13/16</td> <td>249</td> </tr> <tr> <td>19</td> <td>19-5/8</td> <td>498</td> </tr> <tr> <td>20</td> <td>19-15/16</td> <td>506</td> </tr> <tr> <td>29</td> <td>29-1/4</td> <td>743</td> </tr> <tr> <td>30</td> <td>30-1/16</td> <td>764</td> </tr> <tr> <td>39</td> <td>39</td> <td>991</td> </tr> <tr> <td>40</td> <td>40</td> <td>1016</td> </tr> </table>	<u>Code</u>	<u>in</u>	<u>mm</u>	9	9-5/8	244	10	9-13/16	249	19	19-5/8	498	20	19-15/16	506	29	29-1/4	743	30	30-1/16	764	39	39	991	40	40	1016	<p>A</p> <p>Support Core</p> <p>A = Standard Wall Polypropylene Core</p>	<p>TC</p> <p>Cartridge Seal Design</p> <p>DO= Double-Open-End (gasket seal)</p> <p>TC = Single-Open-End (222 O-ring seal)</p>	<p>A</p> <p>End Seal Options</p> <p>A = Polyolefin Foam Gasket (standard for "DO" seal design)</p> <p>N = Buna-N O-Ring (standard for "TC" seal design)</p>
<u>Code</u>	<u>in</u>	<u>mm</u>																													
9	9-5/8	244																													
10	9-13/16	249																													
19	19-5/8	498																													
20	19-15/16	506																													
29	29-1/4	743																													
30	30-1/16	764																													
39	39	991																													
40	40	1016																													

Process Filtration Division

Parker Filtration
Filter Division Europe
Shaw Cross Business Park
Dewsbury, West Yorkshire
WF12 7RD, England
Phone: +44 (0) 1924 487000
Fax: +44 (0) 1924 487001
Website: www.parker.com

